BUNDED WASTE OIL TANKS



Code	ECO710WO	ECO875WO	ECO1100SLWO	ECO1300WO	ECO1450WO
Type	Compact Waste Oil Tank	Low Level Waste Oil Tank	Slimline Waste Oil Tank	Cylindrical Waste Oil Tank	Cylindrical Waste Oil Tank
Diameter	-	1430mm		1430mm	1430mm
Height	520mm	1150mm	1440mm	1570mm	1630mm
Length	850mm	-	1880mm	-	-
Width	420mm	-	700mm	-	-
Filtering	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter
Outlet	-	-		-	-
Weight	75kg	80kg	130kg	80kg	100kg
Capacity	710 litres / 156 gal	875 litres / 192 gal	1000 litres / 235 gal	1300 litres / 285 gal	1500 litres / 330 gal











Code	ECO1600WO	ECO1900SLWO	ECO2000SLWO	ECO2000WO	ECO2500WO
Туре	Cylindrical Waste Oil Tank	Slimline Waste Oil Tank	Cylindrical Waste Oil Tank	Cylindrical Waste Oil Tank	Cylindrical Waste Oil Tank
Diameter	1600mm	-	1450mm	1600mm	2050mm
Height	1450mm	1860mm	2000mm	1640mm	1600mm
Length	-	2365mm	+	-	+
Width	-	840mm		-	
Fill point	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter
Outlet	-	-		-	+
Weight	102kg	125kg	125kg	127kg	127kg
Capacity	1600 litres / 360 gal	1900 litres / 418 gal	2000 litres / 440 gal	2000 litres / 440 gal	2500 litres / 550 gal



Code	ECO3000SLWO	ECO3400WO	ECO4000WO	ECO4500WO	ECO5000WO
Type	Tall Cylindrical	Cylindrical Waste Oil Tank			
	Waste Oil Tank				
Diameter	2250mm	2200mm	2200mm	2200mm	2200mm
Height	1600mm	1350mm	1600mm	1650mm	1950mm
Length	-	-	-	-	-
Width	-	-		-	-
Fill point	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter	16" & 4" mesh filter
Outlet	-	-		-	-
Weight	155kg	150kg	150kg	150kg	150kg
Capacity	3000 litres / 660 gal	3000 litres / 660 gal	4000 litres / 880 gal	4500 litres / 990 gal	5000 litres / 1100 gal

ECOSURE WASTE OIL TANKS

Installation Guidelines and Product Notes

IMPORTANT:

The tank has been fully tested prior to leaving our factory. Please check to ensure that no damage has occurred in transit. If you suspect that it has been damaged, please telephone 01763 261781

PRODUCT DETAILS:

- Suitable for the storage of Kerosene, Fuel Oil and GasOil/Diesel including up to 10% biofuel, lubricants, some chemicals
- Bunded to protect the environment
- Bund contains minimum 110% volume of the inner tank
- Removable filter bowl
- 4" mesh filter
- Made from UV stabilised impact resistant polymer
- Designed and manufactured in the UK

PRODUCT NOTES:

- Tank must be sited on a level, fully supporting concrete base, preferably extending 300mm all around all sides. The base will need to provide continual structural support, even though ground conditions may alter from season to season and year to year
- Do not site the tank tight against a wall
- Do not overfill.
- Fill with buckets or containers through the filter bowl
- To empty, open lid, remove filter bowl, remove 4" filter and insert suction pipe
- Carry out a visual check of the tank annually
- If fitted with optional bund alarm, test regularly

BENEFITS:

- Suitable for commercial, agricultural, & industrial use
- Ideal for garages, factories, workshops, bus depots, transport companies, marinas, etc.
- High impact strength
- Bunded construction offers integral protection from leakage and spillage
- Covered bund prevents collection of rainwater & debris
- Rotationally moulded for strength and durability
- 10 year warranty against manufacturing defects

OPTIONAL EXTRAS — CALL FOR FURTHER DETAILS

- Hasp and staple
- 1" bottom draw off to feed waste oil burner
- Filling connections for pumped waste
- Bund alarm
- High level alarm







Etills Ltd, Unit 1 Whiting Way, Melbourn, Royston, SG8 6NA

