# ECO900OT

Product description: cylindrical open top tank, suitable for internal or external use



Product Information			
Height	Diameter	Weight	Outlet
725mm	1250mm	35kg	2"" BSP

 $\label{thm:continuous} \textbf{Sizes approximate, owing to shrinkage} \\ \textbf{Specification subject to change; please call to confirm details} \\$ 

#### **PRODUCT NOTES:**

- Tank must be sited on a level, fully supportive base leaving a gap of at least 50mm from walls or other tanks
- Additional fittings can be added as and where required without compromising tank's structural integrity

#### **PRODUCT DETAILS:**

- Made from high quality recycled polymer
- Approximate wall thickness: 6-7mm
- 2" brass threaded outlet moulded into tank, as standard
- Can be moulded blank if required

### BENEFITS:

- Suitable for internal and external use
- Frost proof; will not crack in cold
- Value for money, high capacity holding tank
- Ideal for domestic or commercial use
- Robust, heavy duty product; industrial strength
- Smooth sides for easy cleaning
- Rotationally moulded for strength and durability
- 1 year warranty against manufacturing defects

## **OPTIONAL EXTRAS:**

- Brass tap
- Brass isolation valve with hose connector
- Tank connectors
- Ball cock and float valve
- Upgrade to coloured polymer to suit location
- 1" outlet or blank (no outlet)
- Stainless steel outlet



Etills Ltd, Unit 1 Whiting Way, Melbourn, Royston, SG8 6NA