

ECO1275PILPOT

Product description: 1275 litre pillar tank with multiple outlets, manufactured from WRAS approved polymer



Product Information

Height	Width	Depth	Weight	Outlets	Lid
1765mm	1130mm	660mm	75kg	1 x 3/4", 1 x 1 1/2", 1 x 2" BSP	14" screw-down

PRODUCT NOTES:

- Tank must be sited on a level, fully supportive base leaving a gap of at least 50mm from walls or other tanks
- Multiple outlets. Raised tap connection allows containers to be filled. Lower outlets allow tank to be completely drained
- Outlets not drilled unless requested

Sizes approximate, owing to shrinkage

PRODUCT DETAILS:

- Made from WRAS approved polymer
- Approximate wall thickness: 6-7mm
- Non vented 14" screw-down lid as standard
- 3/4" raised brass threaded outlet
- 1 1/2" threaded outlet moulded into tank on left side
- 2" threaded outlet moulded into tank on right side

OPTIONAL EXTRAS:

- Brass tap
- Brass isolation valve
- By-law 30 kit
- Ball cock and float valve
- Tank connectors
- Upgrade to 16" lid

BENEFITS:

- Suitable for internal and external use
- Frost-proof; plastic will not crack in cold
- Plastic meets the requirements of BS 6920-1:2000
- Plastic will not contaminate water
- Modern, minimalist pillar design
- Small footprint maximises capacity when space is limited
- Robust, heavy duty product; industrial strength
- Rotationally moulded for strength & durability
- 2 year warranty against manufacturing defects



Etills Ltd,
Unit 1 Whiting Way,
Melbourn,
Royston,
SG8 6NA



Call 01763 261781